

**B.TECH.****THEORY EXAMINATION (SEM–VIII) 2016-17****MACHINE FOUNDATION DESIGN****Time : 3 Hours****Max. Marks : 100****Note : Be precise in your answer. In case of numerical problem assume data wherever not provided.****SECTION – A****1. Explain the following:****10 x 2 = 20**

- What is meant by Logarithmic decrement?
- Define Damping ratio?
- Mention the types of machine foundation?
- Explain about hammer foundation?
- List the field methods used to determine the dynamic properties of soil?
- What is coefficient of elastic uniform compression?
- Give the importance of vibration isolation in case of machine foundations ?
- List the various isolation materials ?
- Write a note on rotary type machines ?
- Name the commonly used vibration absorbers ?

**SECTION – B****2. Attempt any five of the following questions:****5 x 10 = 50**

- Derive general equation of motion for an undamped free vibration of a single degree of freedom system.
- Find the response of an SDOF system subjected to Harmonic excitation in the form of a Sine wave. A weight of 13.8 N is vertically suspended on a steel wire of length 125 cm and cross sectional area  $6.5 \times 10^{-3} \text{ cm}^2$ . Determine the frequency of free vibrations of the weight. If modulus of elasticity of steel is  $2.12 \times 10^5 \text{ N/mm}^2$ . Determine the amplitude of this, vibration if the initial displacement is 0.025 cm and initial velocity is 2.50 cm/sec.
- How will you determine the natural frequencies of the machine foundation by using Ford and Haddow's method ?
- The coefficient of elastic uniform compression of a soil is found to be  $24000 \text{ kN/m}^3$  using a plate of diameter 4m. What would be percentage variation in its value if the diameter of the plate is halved?
- The following data refers to a block vibration test. Obtain the value of coefficient of uniform elastic compression of the soil. Estimate the spring constant of the system. Weight of machine = 22.50 kN, weight of oscillator = 300 N and size of foundation block is 2.50 m x 3.00 m x 2.00 m height. Determine the value of damping ratio and minimum amplitude. What is the prospect of resonance, if the operating frequency of the oscillator is 600 rpm ?

Frequency of vibration(Hz)	30	36	40	46	49	53	55	58
Amplitude (mm)	0.065	0.095	0.150	0.380	0.430	0.375	0.320	0.270

- What do you understand by the term vibration isolation? Discuss active and passive isolation methods of vibration ?

- (g) What are the properties of the good vibrating isolation material? List out and describe the properties of any two vibration isolating materials.
- (h) Outline the construction guidelines for providing vibration absorbers?

### **SECTION – C**

**Attempt any two of the following questions:**

**2 x 15 = 30**

- 3.
  - (a) Starting from fundamentals, derive the expression for natural frequency of SDOF system of free vibration subjected to damping.
  - (b) A Foundation block of weight 30 kN rest on a soil for which the stiffness may be assumed as 25000 kN/m. The machine is vibrated vertically by an exciting force of  $3.0 \sin(30t)$  kN. Find the natural frequency, natural period, natural circular frequency and the amplitude of vertical displacement. The damping factor is assumed to be 0.50.
- 4.
  - (a) What are seismic wave propagation tests? Explain how the shear modulus is estimated by seismic cross-hole technique?
  - (b) Discuss on the vibration isolation techniques for rigid foundation?
- 5. Summarize the principles of design of foundation for impact type machine with suitable Illustrations?